



STARTER KIT SK25



» Static Cutter for Cutting-height
up to 25 mm





TECHNICAL DATA:

Cutting Table: Static
Max. Cutting height: 25 mm
Working width (Y): 1,60 m / 2,00 m
Total width (incl. bridge): 2,50 m
Working length (X): 3,40 m + 2,40 m Module
Total length: 4,75 m
Max. Cutting Speed: 40 m/min
Max. Positioning Speed: 70 m/min
Max. Acceleration: 4 m/s

Operating voltage: 400 V, 50/60 Hz
Controls / Drive: 2,5 kW
VVacuum Unit: 7,5 kW / 11 kW
Total main power: 10 kW
Fuse: 25 A
Protection class: class 1
Compressed air (5-6 bar): 10 l/min
..... 180 l/min (for drilling device)
Weight: ca. 1.500 kg
Working height: 0,85 m

Cutting head:

Knife size: 2 x 6 mm
Tools: Drilling device
Drawing device

Acoustic level: 57 - 74 dB(A)

Mark of conformity: CE

The SK25 from Kuris, LLC offers all advantages of a fully automatic CNC Cutter with a very attractive value for money. Due to the small dimensions of the cutter, the StarterKit is ideal for small spaces. Sample cuts, small or medium sized series - the Starter Kit from Kuris is the perfect solution, if flexibility, efficiency and accuracy is required for a very convenient price. Based on the established Kuris Technology, this system offers all features, that can also be found at large cutting systems. The cutting height of the StarterKit with up to 25 mm provides a wide field of applications. The cutting window with the dimensions 1.60 m x 3.40 m offers enough space for most cutting orders while the table dimensions are still very compact. The Starter Kit is the perfect system, if easy, fast and economic solutions are required.

The comprehensive product range also allows solutions tailored to your particular needs. In our showroom, spreading and cutting machines are available both for general demonstrations and for testing with your own materials.

Arrange an appointment with us.
We will be delighted to advise you!

Kuris, LLC
2100 Muddy Creek Rd, Blountville, TN 37617
Office: 1 - 423 - 212 - 1217
Fax: 1 - 423 - 374 - 1224
Mobile: 1 - 423 - 571 - 1364
E-Mail: jack@kurisusa.com

Technical changes maybe possible.